

3260-1 ChromaView

TRI-COLOR PORTABLE CHANGEABLE MESSAGE SIGN Small LED Full Matrix – 32 pixels x 60 pixels

CATALOG NO: **AMS30146000**



GENERAL SPECIFICATIONS

The 3260-1 ChromaView from American Signal Company represents the latest advances in ALL-LED sign and highway safety technology. This ALL-LED, Tri-Color, Full Matrix, Graphics capable display, utilizing 30 degree ITE Amber LEDs, gives you an affordable and effective portable / changeable display message sign. With this display, users have the ability to furnish timely, pertinent, and dynamic traffic information to en-route motorists via alphanumeric text and/or graphic display.

Additionally, the 3260-1 ChromaView may be utilized in calming and speed awareness applications through the use of an optional radar interface. This option is capable of not only displaying cautionary traffic messages, but actual vehicular speeds for those exceeding the user selectable "threshold" speed, as well.

FEATURES

- Full Matrix 32 Rows x 60 Columns
- Red, White, & Amber LED's
- 1-5 line messages
- Up to 15 characters per line
- 6" 25" high characters
- Graphics and Animations
- 11 Font sizes
- NTCIP Compliant

OPTIONS

- Cellular (CDMA / IXRTT, GSM / GPRS)
- Landline or Ethernet (TCP / IP) Options
- Radar Overspeed Detection
- Queue Detection
- Onboard CCTV
- AIMSTAR™ Adjustable Solar Assembly
- · Radar Data Logging & Graphing
- Expanded Battery and Solar Packages
- Vehicle Mount

COST EFFECTIVE

- Energy Efficient
- Environmentally Sound

EASY TO USE

- User-friendly
- Local and / or remote sign control

LOW MAINTENANCE


- Long Life LEDs
- SOLR Primary Power Charging

GRAPHICS AND LEGIBILITY

- This Full Matrix Display gives you the power to deliver information via larger text and full sign sized graphics.
- Legibility distance of approximately 800'
- 26 MUTCD symbol signs are available
- 11 character fonts with character heights from 6"-25"
- Full height chevrons, moving arrows







CONTROL / OPERATION

Pre-programmed Messages 200
User-Defined Messages 200
Message Sequences 250
Graphics & Symbols 150
Control Panel Display Backlit LCD

CHARACTER FONTS

Font	Nominal Height	Max. Lines	Max. Characters	Legibility Distance
3x7	9"	4	15	450'
4x7	9"	4	12	500'
5x7	9"	4	10	550'
5x7W*	9"	4	7	600'
7x7	9"	4	8	650'
7x7W*	9"	4	6	700'
6x11	14"	2	7	900'
7x20	25"	1	5	1400'
9x20	25"	1	5	1500'
3x5	6"	5	15	300'
4x5	6"	5	12	350'

PHYSICAL / MECHANICAL

Height (raised) 130" / 3.3m
Height (storage) 94" / 2.4m
Length (tongue) 103" / 2.6m
Length (w/o tongue) 79" / 2.0m
Width 63" / 2.0m
Sign Case Width 79" / 1.6m
Sign Case Height 46" / 1.2m

ELECTRICAL / DISPLAY

Matrix Type	Full Matrix	
LEDs Per Pixel	3	
Angularity	30 Degrees	
Speed-Variable Timing	.10 sec increments	
Matrix Size	32 Rows x 60 Columns	
LED Colors	590 nm Amber / Yellow 630 nm Red 3500 nm White	
Character Size	9" – 25"	

