

CMS-GP232Y ADVANTAGE

Full Matrix - Truck Mount

CATALOG NO: AMS30062326



GENERAL SPECIFICATIONS

The CMS-GP232Y from American Signal Company represents the latest advances in All-LED sign and highway safety technology. With this sign, you can display full sign sized MUTCD regulatory and warning symbols, large sign sized text characters, and three lines of standard text characters. The light weight of the sign case and its small 34" high x 71" wide sign case size allows you to transfer it easily between different trucks, and even to its optional trailer mount.

This full matrix display, utilizing 30 degree ITE amber LEDs gives you the lowest cost and most effective display message sign available today. The wide viewing angle allows the sign to be legible at all times when other signs fade out and are unusable. The menu driven programming includes Amsig's Quick Edit feature, which alllows for one-screen access to create, display, and save user-defined messages.

FEATURES

- Up to 18 Characters Per Line
- 28 Rows x 72 Columns
- 5" to 19" Characters
- 1, 2, 3, or 4-Line Messages
- Graphics and Animations
- 11 Available Font sizes

OPTIONS

- Cellular (CDMA / IXRTT, GSM / GPRS)
- Radar Overspeed Detection
- Queue Detection
- Work Zone Alert Radar
- Radar Data Logging
- ITS Compatible
- WiFi

GRAPHICS AND LEGIBILITY

- 230 Pre-Programmed Messages
- 200 User-Defined Messages
- 250 Message Sequences
- 27 MUTCD Symbol Signs
- 11 Available Font Sizes
- Full Height Chevrons, Moving Arrows
- Ability to Flash Lines or Entire Message
- Incident Management Capability
- Legibility Distance of One Thousand Feet
- Larger Text and Full Sign Sized Graphics

PHYSICAL / MECHANICAL

Electric Screw Actuator	
Sign Case Height	33.9" / 0.9m
Sign Case Width	70.8" / 1.8m
Sign Rotation	pivot pins

ELECTRICAL / DISPLAY

Matrix Type	Full Matrix
Matrix Size	28 Rows x 72 Columns
LED Color	ITE Amber
Character Size	5" to 19"
Update Speed Timing	.10 sec increments



GS-07F-0399L

2755 Bankers Industrial Dr. Atlanta, GA 30360 VOICE: 770.448.6650 FAX: 770.448.8970 info@amsig.com / www.amsig.com * Specifications/Technology is subject to change. v.1.0 JUL 2015