American Signal

CMS-T465
Full Matrix

Get a quote



RELIABLE.
VERSATILE.
HIGH VISIBILITY..

1,000+ FT LEGIBILITY

OPTIONAL SATELLITE CONNECTIVITY

Starlink Mini connectivity available for deployments with limited or no cellular coverage.

POWER SYSTEM

170W solar panel
12V battery system
Perpetual charging in direct sunlight
Onboard AC charger
MPPT solar charge controller

CONTROL & OPERATION

Handheld control terminal
Message scheduling
Automatic brightness adjustment
Password-protected access
Diagnostics and system monitoring

GSA

MAS CONTRACT
47QSMS26D006Z

CMS-T465

SPECIFICATIONS & OPTIONS

DISPLAY SPECIFICATIONS

Display type	Full matrix
Pixel matrix	24 rows × 48 columns
LEDs per pixel	4
Viewing angle	30 degrees

CHARACTER FONTS

Font matrix	Height	Chars per line	Lines
3 × 5	8.5 in.	12	4
4 × 5	8.5 in.	9	4
3 × 7	12 in.	12	3
4 × 7	12 in.	9	3
5 × 7	12 in.	8	3
5 × 7W	12 in.	7	3
7 × 7	12 in.	6	3
7 × 7W	12 in.	5	3
6 × 11	18 in.	7	2
7 × 20	34 in.	3	1
9 × 20	34 in.	3	1

COMPLIANCE & STANDARDS

Meets FHWA standards
MUTCD-compliant messaging
NTCIP Version 2 / V1203 object support
ITE amber LED standards
WYSIWYG message display control

BATTERY UPGRADE

LiFePO4 battery upgrade package
20-year battery life*

PHYSICAL & MECHANICAL

Raised height	11 ft 3.7 in.
Stored height	7 ft 8 in.
Length with tongue	8 ft 7 in.
Length without tongue	6 ft 9 in.
Rear outrigger extension	1 ft 6 in.
Trailer width	5 ft 3 in.
Sign case width	6 ft 6 in.
Sign case height	4 ft 0 in.

MESSAGE MEMORY

230 preprogrammed messages
200 user-defined messages
250 message sequences
150 graphics and animations

CHARACTER FONTS

Font matrix	Height	Chars per line	Lines
3 × 5	13 in.	12	4
4 × 5	13 in.	10	4
3 × 7	18 in.	12	3
4 × 7	18 in.	10	3
5 × 7	18 in.	8	3
5 × 7W	18 in.	7	3
7 × 7	18 in.	6	3
7 × 7W	18 in.	5	3
6 × 11	28 in.	7	2
7 × 20	53 in.	6	1
9 × 20	53 in.	5	1

(770) 448-6650 | amsig.com | info@amsig.com

© American Signal Company. Specifications subject to change without notice. All rights reserved.